

Model: BEMG36 Series

Total Power	36 Watts
Input Voltages	90-264 VAC
Outputs	Single



SPECIAL FEATURES

- Universal Input
- Green Power Design
- RoHS compliant
- EMI meets EN55011 FCC Class B
- Medical Approved EN60601-1/UL2601-1
- CE compliant

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature: 0 to +40°C with no derating

Power Density: 2.87 Watts/Cubic inch

Storage Temperature: -20° to +85°C

Temperature coefficient: ±0.04% / °C

Cooling: Free air convection

SAFETY APPROVALS

EN60601-1/UL2601-1

ELECTRICAL SPECIFICATIONS

Input Specifications

Input Range.....	90-264 VAC
Frequency.....	47-63 Hz
EMI filter.....	EN55011 FCC Class B
Input Connector.....	IEC320-3P AC Receptacle
Inrush Current.....	35A @ 230 VAC
Input Current.....	0.85A @ 90Vac 0.30A @ 264Vac
Dielectric Withstand.....	Meet IEC950
Hold-up Time.....	15mS @ 115Vac 60mS @ 230Vac
Efficiency.....	80%
Green Power.....	0.37W @ 132Vac 0.50W @ 264Vac
Switching Frequency.....	60 KHz.
Leakage.....	<0.126mA

Output Specifications

DC Output.....	Maximum continuous output power 36 Watts.
Line Regulation.....	0.2%
Load Regulation.....	±3.0%
Ripple and Noise.....	1.0% Pk to Pk

300-1 Route 17 South Suite B2
 Lodi, NJ 07644
 Phone: (973) 594-1800 Fax: (973) 594-1804
salesteam@blutekpower.com

Model: BEMG36 Series

ELECTRICAL SPECIFICATIONS (CONT')

Output Specifications

Transient Response..... Output voltage returns in less than 1mS following a 25% load change.

OVP.....Built-in, Zener diode clamping

Overload Protection (OLP).....125% to 150%

Short-circuit Protection

NOTES

- Specifications subject to change without notice.
- All dimensions in inches/mm
- Warranty: 1 year
- Weight: 11.6Oz. (330g)


MODEL No. / OUTPUT VOLTAGE / CURRENT RATINGS CHART (Sample Chart not all Models shown)

Model No.	O/P Voltage (Vdc)	Current
BEMG36-120-72	12.0V	3.0A
BEMG36-200-72	20.0V	1.8A
BEMG36-240-72	24.0V	1.5A
BEMG36-360-72	36.0V	1.0A
BEMG36-480-72	48.0V	0.8A

*All voltages available between 12V and 48V in increments of .1V
Various output connectors available*

MECHANICAL DIMENSIONS: MM [INCHES]

WEIGHT: 330.0g (11.6 Oz.)



300-1 Route 17 South Suite B2
Lodi, NJ 07644
Phone: (973) 594-1800 Fax: (973) 594-1804
salesteam@blutepower.com